



# FARCO FLEX PRIMER

## Polyurethane and Polysulphide Sealant Primer

### Product Description

FARCOFLEX PRIMER is a one component fast drying liquid primer for improving the adhesion properties of sealants to variety of substrates in harsh environment.

#### ● Application

- Masonry , natural stone , concrete
- On most dusty, porous or friable substrates
- Increases adhesion of pu-sealants to metal, glass, aluminum and synthetic materials.

#### ● Advantages

- Ensures adhesion of polyurethane sealants to most substrates.
- Reinforced dusty , porous and friable materials
- Increases adhesion for use in immersion situations

#### ● Technical Data

Type	viscous liquid
Density	0.93
Viscosity	50 mPa.s at 20°C
Flash point	55°C
Drying time	30min to 1 hour depending upon Temperature

#### ● Coverage

From 100 to 250 ml/m<sup>2</sup> depending upon

the porosity of substrates.

#### ● Method of use

- Apply with dry and clean paint brush.
- Apply only a thin film on glazed or metallic substrates.
- Saturates porous substrates.

#### ● Cleaning

Material: immediately with solvent

Hands: soap and water.

#### ● Packaging

FARCOFLEX PRIMER is supplied in 1 liter containers.

#### ● Shelf life

1 year in original, unopened container, at temperatures +5 to +25°C.

#### ● Safety and Handling Precautions

First category flammable liquid.

#### ● Technical Service

The SHIMISAKHTEMAN Technical Service Department is available to assist you in the correct use of our products in the field.



242 Bldg., Mirdamad Blvd., After Naft St., Tehran. Iran

Tel: +98 21 (22263100 , 22263099 , 22259736) Fax: +98 21 22260586

Shimi Sakhteman



+98 21 27427