

# FARCO TEK S4 (SEALANTICO)

## High Gloss Waterproofing and Penetrating Sealer

### Product Description

S4 is a high gloss, UV Resistant sealer intended for all types of concrete, wood, bricks, stones and cementitious grouts. S4 offers improved resistance to rain, sun, freezing temperatures, stains, and other pollutants that sometimes can be hazardous to these kinds of surfaces. It also contains penetrating silicone resins for water repellency improvement.

#### ● Application

- High Gloss Waterproofing and Penetrating Sealer for exterior and interior surfaces
- Suitable for artificial and natural stones in public areas and bathrooms
- Brick and stone floors, wood and concrete

#### ● Advantages

- Penetration ability into substrates
- High adhesion properties to most of the surfaces
- UV resistant
- Resistant in hot and cold climates
- Good abrasion resistance in residential areas
- Resistant to the usual cleaning agents
- Protecting the surfaces against dirt pick up
- Protecting the surfaces against efflorescence

#### ● Typical physical properties

Wet Appearance	Clear to lightly cloudy liquid
Dry Appearance	Clear, Glossy
Specific gravity	0.9±0.02 kg/l
Dry film thickness	20-50 µm

#### ● Coverage

- 70 to 150 gr/m<sup>2</sup>
- Apply 2 layers with 24 hours interval

#### ● Preparation and Application

- The substrate must be sound, firm, clean and free of oil, grease, loose particles, cement laitance, old layers of paint or other contaminants.
- Wait 24 to 72 hours after rain; do not apply if rain is forecast within 24 hours. In order to avoid efflorescence and delamination do not apply on wet surfaces.
- Apply with brush or spray
- If lower gloss is needed, dilute with aromatic solvents
- S4 is a fast drying sealer which is usable after 24 hours

#### ● Packaging

P7 is supplied in 1, 4 and 20 kg gallons.

#### ● Storage and Shelf life

6 month when stored in dry and cool place in original and unopened container

# FARCO TEK S4 (SEALANTICO)

## ● Safety and Handling Precautions

Use the product with adequate ventilation and personal protection. Do not store or apply in vicinity of open flame

## ● Technical Service

The SHIMISAKHTEMAN Technical Service Department is available to assist you in the correct use of our products in the field.



242 Bldg., Mirdamad Blvd., After Naft St., Tehran. Iran  
Tel: +98 21 (22263100 , 22263099 , 22259736) Fax:+98 21 22260586



+98 21 27427