

SHIMO TEN

Paint for all mineral substrates such as concrete, cement and cement-lime plaster, With high flexibility

Product Description

SHIMOTEN is a water-borne paint with a high quality acrylate dispersion binder.

● Application

- Building facades
- Indoor and outdoor of Villas next to the sea
- Indoor and outdoor walls of food industry factories
- Painting of parking, sport and public halls walls
- For painting swimming pool ceiling
- For painting cement board roof top

● Advantages

- Crack bridging paint with good flexibility
- It offers very good weather and water resistance
- Environmentally friendly, no petroleum solvent added
- Easy to apply

● Technical Data

PH	8-9
Viscosity	130 to 140 Krebs
Resistance to scrubbing ASTM D3450	Passed
Grain size	≤20 μm
Drying time ASTM D1640	Less than 1 hour
Shine ASTM D528	29

● Method of use

- It can be applied in two to three coats by means of brush, roller or spray machine
- Wait until the first coat is completely dry before applying the second coat
- SHIMOTEN must be applied on dry and clean substrate (free from any substances such as oil, dust, loose materials and etc)
- Traditional cement plasters, lime cement plasters and gypsum substrates (age over 15 days)
- Use the diluted form of SHIMO TEN as a primer
- For crack filling use FARCOTOP 50 (KAS-MATIC) in combination with FARCOTOP SA12

● Coverage

3-8m²/kg Depending on the permeability and surface roughness

● Packaging

SHIMOTEN is supplied in 5 and 12 pails.

● Storage and Shelf life

Keep In a dry place, away from direct sunlight and extreme temperature. Shelf life is 1 years in unopened containers



242 Bldg., Mirdamad Blvd., After Naft St., Tehran. Iran

Tel: +98 21 (22263100 , 22263099 , 22259736) Fax: +98 21 22260586

Shimi Sakhteman



+98 21 27427